23 nfc 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 18 March 2004 (18.03.2004)

(10) International Publication Number WO 2004/023514 A1

(51) International Patent Classification7:

H01J 37/20

(21) International Application Number:

PCT/NL2003/000467

(22) International Filing Date:

24 June 2003 (24.06.2003)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data: 1020936

25 June 2002 (25.06.2002)

(71) Applicant (for all designated States except US): TECH-NISCHE UNIVERSITEIT DELFT [NI/NL]; Julianalaan 134, NL-2628 BL Delft (NL).

- (75) Inventor/Applicant (for US only): ZANDBERGEN, Hendrik, Willem [NL/NL]; De Hoop 11, NL-2223 BZ Katwijk (NL).
- (74) Agent: PRINS, A.W.; NIEUWE PARKLAAN 97, NL-2587 BN DEN HAAG (NL).


- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model). CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EB, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, I.C., LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW. MX. MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, 2M, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM. KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, T1, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, EE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCI Gazette.

(54) Title: SPECIMEN HOLDER FOR AN ELECTRON MICROSCOPE, AND METHOD FOR REDUCING THERMAL DRIFT IN A MICROSCOPE



(57) Abstract: A specimen holder for an electron microscope, comprising a rod-shaped part, which is provided near one end with a tip, which tip is arranged to receive a specimen, the rod-shaped part, in use, extending with at least the tip into the electron microscope. held by clamping means present in the electron microscope, wherein first temperature control means are provided to control the temperature of the rod-shaped part and/or the clamping means, such that this rod-shaped part and the clamping means substantially have the same temperature, at least at the location of their contact surfaces.